PAXTON ET AL. -- 10/783,088 Client/Matter: 081468-0304351

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A thermal processing apparatus, comprising: at least one heating element;

a heat distributing plate, having a heating surface and being disposed in thermal communication with the at least one heating element, the heat distributing plate being constructed and arranged to distribute heat from the heating element onto the heating surface;

a substrate support, constructed and arranged to support a substrate at a position above the heating surface; and

an actuator, constructed and arranged to rotate the substrate during a heat transfer operation; and

a drift controlling structure configured to control a lateral movement of the substrate relative to the heat distributing plate and/or rotate the substrate.

- 2. (Original) A thermal processing apparatus according to claim 1, wherein the substrate support is rotated by the actuator to transmit rotation of the actuator to the substrate.
- 3. (Original) A thermal processing apparatus according to claim 1, wherein the at least one heating element comprises an array of heating elements.
- 4. (Currently Amended) A thermal processing apparatus according to <u>claim 3</u> elaim 1, wherein at least two heating elements of the array of heating elements are independently controllable.
- 5. (Original) A thermal processing apparatus according to claim 1, wherein the substrate support further comprises a plurality of spheres disposed such that at least a portion of each of the spheres extends beyond the heat transfer surface and the spheres are rotatable by action of the actuator to transmit rotational motion to the substrate.

PAXTON ET AL. -- 10/783,088

Client/Matter: 081468-0304351

6. (Original) A thermal processing apparatus according to claim 5, wherein the plurality

of spheres comprises exactly three spheres and the spheres comprise a thermally insulating

material.

7. (Cancelled).

8. (Currently Amended) A thermal processing apparatus according to claim 1 elaim 7,

wherein the drift controlling structure comprises a plurality of members constructed and

arranged to contact an edge of the substrate.

9. (Original) A thermal processing apparatus according to claim 8, wherein the

members contact the edge of the substrate consistently during processing.

10. (Original) A thermal processing apparatus according to claim 8, wherein the

members contact the edge of the substrate intermittently, when the substrate has drifted

beyond a predetermined acceptable range.

11. (Original) A thermal processing apparatus according to claim 8, wherein the

members further comprise rotatable members in contact with the edge of the substrate.

12. (Currently Amended) A thermal processing apparatus according to claim 11, wherein

the rotatable wheels members are drivable by the actuator such that they exert a rotational

force on the substrate and thereby act as the actuator to rotate the substrate.

13. (Original) A thermal processing apparatus according to claim 1, wherein the substrate

support comprises a gas bearing.

14. (Original) A thermal processing apparatus according to claim 13, wherein the gas

bearing is controllable to act as the actuator.

15. (Cancelled).

- 3 -

PAXTON ET AL. -- 10/783,088 Client/Matter: 081468-0304351

16. (Original) A thermal processing apparatus according to claim 13, further comprising a temperature controlling unit constructed and arranged to control a temperature of a gas used to form the gas bearing.

17. (Currently Amended) A method of thermally processing a substrate comprising: heating a heat distributing plate to create a predetermined temperature profile at a heating surface thereof;

placing the substrate above and in thermal communication with the heating surface such that heat is transferred from the heating surface to the substrate; and

rotating the substrate relative to the heating surface such that variations in the temperature profile transferred to the substrate are reduced; and

controlling a drift of the rotating substrate to provide additional control of temperature across the substrate so as to further reduce variation in the temperature profile transferred to the substrate.

- 18. (New) A thermal processing apparatus according to claim 1, wherein said heating element is controllable such that the substrate is heated substantially uniformly.
- 19. (New) A thermal processing apparatus according to claim 1, wherein the substrate support has a relatively small area of contact with the substrate such that the support interferes minimally with distribution of heat radiated from the heating surface.
- 20. (New) A thermal processing apparatus according to claim 1, wherein the drift controlling structure comprises a plurality of pins, a plurality of idler wheels or a combination thereof.
- 21. (New) A thermal processing apparatus according to claim 1, wherein the drift controlling structure comprises a plurality of wheels adapted to engage an edge of the substrate.
- 22. (New) A thermal processing apparatus, comprising: at least one heating element;

a heat distributing plate, having a heating surface and being disposed in thermal communication with the at least one heating element, the heat distributing plate being constructed and arranged to distribute heat from the heating element onto the heating surface;

a substrate support, constructed and arranged to support a substrate at a position above the heating surface; and

an actuator, constructed and arranged to rotate the substrate during a heat transfer operation,

wherein the substrate support comprises a plurality of spheres disposed such that at least a portion of each of the spheres extends beyond the heat transfer surface and the spheres are rotatable by action of the actuator to transmit rotational motion to the substrate.

- 23. (New) A thermal processing apparatus according to claim 22, wherein the plurality of spheres comprises exactly three spheres and the spheres comprise a thermally insulating material.
- 24. (New) A thermal processing apparatus, comprising:

at least one heating element;

a heat distributing plate, having a heating surface and being disposed in thermal communication with the at least one heating element, the heat distributing plate being constructed and arranged to distribute heat from the heating element onto the heating surface;

a substrate support, constructed and arranged to support a substrate at a position above the heating surface; and

an actuator, constructed and arranged to rotate the substrate during a heat transfer operation,

wherein the substrate support comprises a gas bearing and the gas bearing is controllable to act as the actuator.

25. (New) A thermal processing apparatus according to claim 24, further comprising a temperature controlling unit constructed and arranged to control a temperature of a gas used to form the gas bearing.